

### HDINW SERIES

- Heavy Duty **STANDARD** cable (Ø 8mm Urethane: oil-, heat- and fuel-proof).

To be installed between MXN camera and MXN monitor/LCD. It is important to measure the required cable length(s) before purchasing a camera system. This cable has a waterproof female connector (IP67, 4-pin mini DIN) on the camera side and a normal male connector (4-pin mini DIN) on the monitor/LCD side. Available models as below:



#### HDINW5M

- 5 meter urethane, STANDARD cable (IP female~male)

#### HDINW10M

- 10 meter urethane, STANDARD cable (IP female~male)

#### HDINW15M

- 15 meter urethane, STANDARD cable (IP female~male)

#### HDINW20M

- 20 meter urethane, STANDARD cable (IP female~male)

### HDINWW SERIES

- Heavy Duty **EXTENSION** cable (Ø 8mm Urethane: oil-, heat- and fuel-proof).

To be installed between an existing STANDARD cable (see above) and MXN camera. Or to be installed between a Trailerset CAMSOCKET-F and MXN camera. It is important to measure the required cable length(s) before purchasing a camera system. This cable has a waterproof male & female connector (IP67, 4-pin mini DIN) on each side. Available models as below:



#### HDINWW5M

- 5 meter urethane, EXTENSION cable (IP female~IP male)

#### HDINWW10M

- 10 meter urethane, EXTENSION cable (IP female~IP male)

#### HDINWW15M

- 15 meter urethane, EXTENSION cable (IP female~IP male)

#### HDINWW20M

- 20 meter urethane, EXTENSION cable (IP female~IP male)